

PARKOO®

DEHUMIDIFIER

MODEL	PBD608P
POWER SOURCE	208~240V/60Hz
RATED POWER	5000W
RATED CURRENT	23A
MOISTURE REMOVAL (65°F, 60%RH)	200 Pints/Day
MOISTURE REMOVAL (80°F, 60%RH)	335 Pints/Day
MOISTURE REMOVAL (86°F, 80%RH)	560 Pints/Day
MOISTURE REMOVAL (95°F, 90%RH)	700 Pints/Day
INPUT POWER (65°F, 60%RH)	3000 W
INPUT CURRENT (65°F, 60%RH)	13.6A
MOTOR FLA	1.4A
MOTOR COMPRESSOR	RLA:21.6A LRA:80A
REFRIGERANT	R32/1500g
MAXIMUM ALLOWABLE PRESSURE	6.5MPa
MAXIMUM OPERATING PRESSURE HIGH	4.0MPa
MAXIMUM OPERATING PRESSURE LOW	1.7MPa
SERIAL NO.	250300037
DATE MANUFACTURED	03/2025

MADE IN CHINA



Intertek
5007959

CONFORMS TO UL STD. 60335-1 & 60335-2-40
CERTIFIED TO CSA STD. C22.2
NO.60335-1 & 60335-2-40

WARNING - Risk Of Fire.

Flammable Refrigerant Used. To Be Repaired Only By Trained Service Personnel. Do Not Puncture Refrigerant Tubing.

AVERTISSEMENT - Risque d'incendie.

Frigorigène inflammable utilisé. La réparation doit être faite seulement par un personnel qualifié. Ne pas perforer la conduite de frigorigène.

WARNING - Risk Of Fire.

Dispose Of Properly In Accordance With Federal Or Local Regulations. Flammable Refrigerant Used.

AVERTISSEMENT - Risque d'incendie.

Éliminer convenablement conformément à la réglementation fédérale ou locale Frigorigène inflammable utilisé.



Refrigerant
Safety Group
A2L



REMINDER

1. The device remains upright, it will be damaged if to upside down.
- ★2. After confirming that the boom is fixed with nuts, move device to the ceiling. Adjust the it to be parallel to the ceiling level). The tilt of the device will cause abnormal drainage and water leakage.
3. Ensure that the outlet is free from covering, If it is connected to the air duct, lock the air duct, and keep it close to the outlet.
4. For security, connect the ground cable to the device before using it.